

Package: clash (via r-universe)

July 3, 2024

Title Access the Clash of Clans API

Version 0.0.1

Description Interfaces with the official API for Clash of Clans

<<https://developer.clashofclans.com/#/>>. Provides tools to work with players, clans, wars, raids, and other game events. All outputs are provided in a tidy format, where each player, clan, or attack is an observation.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Imports cli, dplyr, httr2, purrr, stringr, tibble, tidyR

Suggests httpTest2, testthat (>= 3.0.0)

Config/testthat.edition 3

URL <https://github.com/christopherkenny/clash>,

<http://christophertkenny.com/clash/>

BugReports <https://github.com/christopherkenny/clash/issues>

Repository <https://christopherkenny.r-universe.dev>

RemoteUrl <https://github.com/christopherkenny/clash>

RemoteRef HEAD

RemoteSha d295d7c949be9738f790673e1793ae82dcc7ffdf

Contents

| | |
|--|---|
| coc_get_builderbase_league | 2 |
| coc_get_builderbase_leagues | 3 |
| coc_get_capital_league | 4 |
| coc_get_capital_leagues | 5 |
| coc_get_capital_raid_seasons | 5 |
| coc_get_clan | 6 |

| | |
|--|----|
| <i>coc_get_clan_labels</i> | 7 |
| <i>coc_get_clan_members</i> | 8 |
| <i>coc_get_clan_search</i> | 8 |
| <i>coc_get_goldpass</i> | 10 |
| <i>coc_get_league</i> | 10 |
| <i>coc_get_leagues</i> | 11 |
| <i>coc_get_league_seasons</i> | 12 |
| <i>coc_get_location</i> | 12 |
| <i>coc_get_locations</i> | 13 |
| <i>coc_get_player</i> | 14 |
| <i>coc_get_player_labels</i> | 15 |
| <i>coc_get_ranking_builderbase_clans</i> | 15 |
| <i>coc_get_ranking_builderbase_players</i> | 16 |
| <i>coc_get_ranking_capitals</i> | 17 |
| <i>coc_get_ranking_clans</i> | 18 |
| <i>coc_get_ranking_players</i> | 19 |
| <i>coc_get_ranking_versus_clans</i> | 20 |
| <i>coc_get_ranking_versus_players</i> | 21 |
| <i>coc_get_war_current</i> | 22 |
| <i>coc_get_war_league</i> | 22 |
| <i>coc_get_war_leagues</i> | 23 |
| <i>coc_get_war_log</i> | 24 |
| <i>key</i> | 25 |
| <i>set_clash_key</i> | 25 |

Index**27*****coc_get_builderbase_league****Get information for one Builder Base league***Description**

Get information for one Builder Base league

Usage

```
coc_get_builderbase_league(
    league,
    limit = NULL,
    after = NULL,
    before = NULL,
    key = coc_get_key()
)
```

Arguments

| | |
|--------|--|
| league | league id, such as 44000041 |
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: get_clash_key() |

Value

tibble with list columns for clan, clans, and history.

Examples

```
coc_get_builderbase_league(league = '44000041', limit = 10)
```

coc_get_builderbase_leagues
Get Builder Base Leagues

Description

Get Builder Base Leagues

Usage

```
coc_get_builderbase_leagues(  
  limit = NULL,  
  after = NULL,  
  before = NULL,  
  key = coc_get_key()  
)
```

Arguments

| | |
|--------|--|
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: get_clash_key() |

Value

tibble with list columns for clan, clans, and history.

Examples

```
coc_get_builderbase_leagues(limit = 10)
```

coc_get_capital_league

Get information for one capital league

Description

Get information for one capital league

Usage

```
coc_get_capital_league(  
  league,  
  limit = NULL,  
  after = NULL,  
  before = NULL,  
  key = coc_get_key()  
)
```

Arguments

| | |
|--------|--|
| league | league id, such as 85000022 |
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: get_clash_key() |

Value

tibble with list columns for clan, clans, and history.

Examples

```
coc_get_capital_league(league = '85000022', limit = 10)
```

```
coc_get_capital_leagues
```

Get Capital Leagues

Description

Get Capital Leagues

Usage

```
coc_get_capital_leagues(  
  limit = NULL,  
  after = NULL,  
  before = NULL,  
  key = coc_get_key()  
)
```

Arguments

| | |
|--------|--|
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: get_clash_key() |

Value

tibble with list columns for clan, clans, and history.

Examples

```
coc_get_capital_leagues(limit = 10)
```

```
coc_get_capital_raid_seasons
```

Get Capital Raid Seasons

Description

Get Capital Raid Seasons

Usage

```
coc_get_capital_raid_seasons(
  clan,
  limit = NULL,
  after = NULL,
  before = NULL,
  key = get_clash_key()
)
```

Arguments

| | |
|--------|---|
| clan | Required. Clan tag. |
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: <code>get_clash_key()</code> |

Value

a tibble with list columns for clan, clans, and history.

Examples

```
coc_get_capital_raid_seasons(clan = '8UC2J90Y')
```

| | |
|--------------|-------------------|
| coc_get_clan | <i>Get a clan</i> |
|--------------|-------------------|

Description

Gets full clan details

Usage

```
coc_get_clan(clan, key = get_clash_key())
```

Arguments

| | |
|------|---|
| clan | Required. Clan tag. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: <code>get_clash_key()</code> |

Value

a tibble with each row as a player

Examples

```
coc_get_clan(clan = '8UC2J90Y')
```

```
coc_get_clan_labels      Get clan labels
```

Description

Get clan labels

Usage

```
coc_get_clan_labels(  
  limit = NULL,  
  after = NULL,  
  before = NULL,  
  key = get_clash_key()  
)
```

Arguments

| | |
|--------|---|
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashroyale.com/#/documentation Default: cr_get_key() |

Value

tibble of card info

Examples

```
coc_get_clan_labels()
```

`coc_get_clan_members` *Get current clan members*

Description

Get current clan members

Usage

```
coc_get_clan_members(  
  clan,  
  limit = NULL,  
  after = NULL,  
  before = NULL,  
  key = coc_get_key()  
)
```

Arguments

| | |
|--------|---|
| clan | Required. Clan tag. |
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: <code>get_clash_key()</code> |

Value

tibble with list columns for clan, clans, and history.

Examples

```
coc_get_clan_members(clan = '8UC2J90Y')
```

`coc_get_clan_search` *Search Clans*

Description

Search Clans

Usage

```
coc_get_clan_search(  
  name = NULL,  
  location_id = NULL,  
  war_frequency = NULL,  
  min_members = NULL,  
  max_members = NULL,  
  min_clan_points = NULL,  
  min_clan_level = NULL,  
  limit = NULL,  
  after = NULL,  
  before = NULL,  
  label_ids = NULL,  
  key = get_clash_key()  
)
```

Arguments

| | |
|-----------------|--|
| name | Search clans by name |
| location_id | Filter by clan location identifier |
| war_frequency | Filter by war frequency |
| min_members | Filter by minimum number of clan members |
| max_members | Filter by maximum number of clan members |
| min_clan_points | minimum amount of clan points |
| min_clan_level | minimum clan level |
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| label_ids | comma separated vector to filter results by |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: get_clash_key() |

Value

a tibble with each row as a player

Examples

```
coc_get_clan_search('Dusty Death', limit = 5)
```

`coc_get_goldpass` *Get Gold Pass Season Information*

Description

Get Gold Pass Season Information

Usage

```
coc_get_goldpass(key = get_clash_key())
```

Arguments

| | |
|-----|---|
| key | Required. API key. See https://developer.clashroyale.com/#/documentation Default: cr_get_key() |
|-----|---|

Value

a tibble of gold pass info

Examples

```
coc_get_goldpass()
```

`coc_get_league` *Get information for one league*

Description

Get information for one league

Usage

```
coc_get_league(  
  league,  
  season,  
  limit = NULL,  
  after = NULL,  
  before = NULL,  
  key = coc_get_key()  
)
```

Arguments

| | |
|--------|--|
| league | league id, such as 29000022 |
| season | season id, such as '2022-09' |
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: get_clash_key() |

Value

tibble with list columns for clan, clans, and history.

Examples

```
coc_get_league(league = '29000022', season = '2022-09', limit = 10)
```

coc_get_leagues *Get Leagues*

Description

Get Leagues

Usage

```
coc_get_leagues(limit = NULL, after = NULL, before = NULL, key = coc_get_key())
```

Arguments

| | |
|--------|--|
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: get_clash_key() |

Value

tibble with list columns for clan, clans, and history.

Examples

```
coc_get_leagues(limit = 10)
```

`coc_get_league_seaons` *Get seasons for one league*

Description

Get seasons for one league

Usage

```
coc_get_league_seaons(
  league,
  limit = NULL,
  after = NULL,
  before = NULL,
  key = coc_get_key()
)
```

Arguments

| | |
|--------|---|
| league | league id, such as 29000022 |
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: <code>get_clash_key()</code> |

Value

tibble with list columns for clan, clans, and history.

Examples

```
coc_get_league_seaons(league = '29000022', limit = 10)
```

`coc_get_location` *Get information for one location*

Description

Get information for one location

Usage

```
coc_get_location(  
  location,  
  limit = NULL,  
  after = NULL,  
  before = NULL,  
  key = coc_get_key()  
)
```

Arguments

| | |
|----------|--|
| location | location id, such as 32000249 |
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: get_clash_key() |

Value

tibble of card info

Examples

```
coc_get_location(location = 32000249)
```

coc_get_locations *Get Locations*

Description

Get Locations

Usage

```
coc_get_locations(  
  limit = NULL,  
  after = NULL,  
  before = NULL,  
  key = coc_get_key()  
)
```

Arguments

| | |
|---------------------|---|
| <code>limit</code> | number of items returned in the response. |
| <code>after</code> | return only items that occur after this marker. |
| <code>before</code> | return only items that occur before this marker. |
| <code>key</code> | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: <code>get_clash_key()</code> |

Value

tibble of card info

Examples

```
coc_get_locations()
```

| | |
|-----------------------------|----------------------------|
| <code>coc_get_player</code> | <i>Get a single player</i> |
|-----------------------------|----------------------------|

Description

Gets the player details for one player.

Usage

```
coc_get_player(tag, key = get_clash_key())
```

Arguments

| | |
|------------------|---|
| <code>tag</code> | Required. The player to return. |
| <code>key</code> | Required. API key. See https://developer.clashofclans.com/#/documentation Default: <code>get_clash_key()</code> |

Value

a tibble of player info

Examples

```
coc_get_player('92GCQQYP')
```

```
coc_get_player_labels  Get player labels
```

Description

Get player labels

Usage

```
coc_get_player_labels(  
  limit = NULL,  
  after = NULL,  
  before = NULL,  
  key = get_clash_key()  
)
```

Arguments

| | |
|--------|---|
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashroyale.com/#/documentation Default: cr_get_key() |

Value

tibble of card info

Examples

```
coc_get_player_labels()
```

```
coc_get_ranking_builderbase_clans  
Get Builder Base Clan Rankings
```

Description

Get Builder Base Clan Rankings

Usage

```
coc_get_ranking_builderbase_clans(
  location,
  limit = NULL,
  after = NULL,
  before = NULL,
  key = coc_get_key()
)
```

Arguments

| | |
|----------|--|
| location | location id, such as 32000249 |
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: get_clash_key() |

Value

tibble of card info

Examples

```
coc_get_ranking_builderbase_clans(location = 32000249)
```

coc_get_ranking_builderbase_players
Get Builder Base Player Rankings

Description

Get Builder Base Player Rankings

Usage

```
coc_get_ranking_builderbase_players(
  location,
  limit = NULL,
  after = NULL,
  before = NULL,
  key = coc_get_key()
)
```

Arguments

| | |
|----------|--|
| location | location id, such as 32000249 |
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: get_clash_key() |

Value

tibble of card info

Examples

```
coc_get_ranking_builderbase_players(location = 32000249)
```

coc_get_ranking_capitals
Get Capitals Rankings

Description

Get Capitals Rankings

Usage

```
coc_get_ranking_capitals(  
  location,  
  limit = NULL,  
  after = NULL,  
  before = NULL,  
  key = coc_get_key()  
)
```

Arguments

| | |
|----------|--|
| location | location id, such as 32000249 |
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: get_clash_key() |

Value

tibble of card info

Examples

```
coc_get_ranking_capitals(location = 32000249)
```

coc_get_ranking_clans *Get Clan Rankings*

Description

Get Clan Rankings

Usage

```
coc_get_ranking_clans(  
  location,  
  limit = NULL,  
  after = NULL,  
  before = NULL,  
  key = coc_get_key()  
)
```

Arguments

| | |
|----------|--|
| location | location id, such as 32000249 |
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: get_clash_key() |

Value

tibble of card info

Examples

```
coc_get_ranking_clans(location = 32000249)
```

`coc_get_ranking_players`
Get Player Rankings

Description

Get Player Rankings

Usage

```
coc_get_ranking_players(  
  location,  
  limit = NULL,  
  after = NULL,  
  before = NULL,  
  key = coc_get_key()  
)
```

Arguments

| | |
|----------|--|
| location | location id, such as 32000249 |
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: get_clash_key() |

Value

tibble of card info

Examples

```
coc_get_ranking_players(location = 32000249)
```

`coc_get_ranking_versus_clans`
Get Versus Clan Rankings

Description

Get Versus Clan Rankings

Usage

```
coc_get_ranking_versus_clans(  
  location,  
  limit = NULL,  
  after = NULL,  
  before = NULL,  
  key = coc_get_key()  
)
```

Arguments

| | |
|----------|---|
| location | location id, such as 32000249 |
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: <code>get_clash_key()</code> |

Value

tibble of card info

Examples

```
coc_get_ranking_versus_clans(location = 32000249)
```

coc_get_ranking_versus_players
Get Versus Player Rankings

Description

Get Versus Player Rankings

Usage

```
coc_get_ranking_versus_players(  
  location,  
  limit = NULL,  
  after = NULL,  
  before = NULL,  
  key = coc_get_key()  
)
```

Arguments

| | |
|----------|--|
| location | location id, such as 32000249 |
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: get_clash_key() |

Value

tibble of card info

Examples

```
coc_get_ranking_versus_players(location = 32000249)
```

`coc_get_war_current` *Get current Clan War*

Description

Get current Clan War

Usage

```
coc_get_war_current(
  clan,
  limit = NULL,
  after = NULL,
  before = NULL,
  key = get_clash_key()
)
```

Arguments

| | |
|---------------------|---|
| <code>clan</code> | Required. Clan tag. |
| <code>limit</code> | number of items returned in the response. |
| <code>after</code> | return only items that occur after this marker. |
| <code>before</code> | return only items that occur before this marker. |
| <code>key</code> | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: <code>get_clash_key()</code> |

Value

tibble with list columns for clan, clans, and history.

Examples

```
coc_get_war_current(clan = '8UC2J90Y')
```

`coc_get_war_league` *Get information for one war league*

Description

Get information for one war league

Usage

```
coc_get_war_league(  
  league,  
  limit = NULL,  
  after = NULL,  
  before = NULL,  
  key = coc_get_key()  
)
```

Arguments

| | |
|--------|--|
| league | league id, such as 48000018 |
| limit | number of items returned in the response. |
| after | return only items that occur after this marker. |
| before | return only items that occur before this marker. |
| key | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: get_clash_key() |

Value

tibble with list columns for clan, clans, and history.

Examples

```
coc_get_war_league(league = 48000018, limit = 10)
```

```
coc_get_war_leagues      Get War Leagues
```

Description

Get War Leagues

Usage

```
coc_get_war_leagues(  
  limit = NULL,  
  after = NULL,  
  before = NULL,  
  key = coc_get_key()  
)
```

Arguments

| | |
|---------------------|---|
| <code>limit</code> | number of items returned in the response. |
| <code>after</code> | return only items that occur after this marker. |
| <code>before</code> | return only items that occur before this marker. |
| <code>key</code> | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: <code>get_clash_key()</code> |

Value

tibble with list columns for clan, clans, and history.

Examples

```
coc_get_war_leagues(limit = 10)
```

`coc_get_war_log`

Get Clan War Log

Description

Get Clan War Log

Usage

```
coc_get_war_log(
  clan,
  limit = NULL,
  after = NULL,
  before = NULL,
  key = coc_get_key()
)
```

Arguments

| | |
|---------------------|---|
| <code>clan</code> | Required. Clan tag. |
| <code>limit</code> | number of items returned in the response. |
| <code>after</code> | return only items that occur after this marker. |
| <code>before</code> | return only items that occur before this marker. |
| <code>key</code> | Required. API key. See https://developer.clashofclans.com/#/documentation . Default: <code>get_clash_key()</code> |

Value

tibble with list columns for clan, clans, and history.

Examples

```
coc_get_war_log(clan = '8UC2J90Y')
```

| | |
|-----|--|
| key | <i>Check or Get Clash of Clans API Key</i> |
|-----|--|

Description

Check or Get Clash of Clans API Key

Usage

```
has_clash_key()  
get_clash_key()  
coc_get_key()  
coc_has_key()
```

Value

logical if has, key if get

Examples

```
has_clash_key()
```

| | |
|---------------|----------------------------------|
| set_clash_key | <i>Add Entry to Renvironment</i> |
|---------------|----------------------------------|

Description

Adds Clash of Clans API key to .Renvironment.

Usage

```
set_clash_key(key, overwrite = FALSE, install = FALSE)  
coc_set_key(key, overwrite = FALSE, install = FALSE)
```

Arguments

| | |
|-----------|---|
| key | Character. API key to add to add. |
| overwrite | Defaults to FALSE. Boolean. Should existing COC_KEY in Renviron be overwritten? |
| install | Defaults to FALSE. Boolean. Should this be added '("~/Renviron' file? |

Value

key, invisibly

Examples

```
## Not run:  
set_clash_key('1234')  
  
## End(Not run)
```

Index

- * **clan**
 - coc_get_capital_raid_seasons, 5
 - coc_get_clan, 6
 - coc_get_clan_members, 8
 - coc_get_clan_search, 8
 - coc_get_war_current, 22
 - coc_get_war_log, 24
 - * **goldpass**
 - coc_get_goldpass, 10
 - * **labels**
 - coc_get_clan_labels, 7
 - coc_get_player_labels, 15
 - * **league**
 - coc_get_builderbase_league, 2
 - coc_get_builderbase_leagues, 3
 - coc_get_capital_league, 4
 - coc_get_capital_leagues, 5
 - coc_get_league, 10
 - coc_get_league_seaons, 12
 - coc_get_leagues, 11
 - coc_get_war_league, 22
 - coc_get_war_leagues, 23
 - * **locations**
 - coc_get_location, 12
 - coc_get_locations, 13
 - coc_get_ranking_builderbase_clans, 15
 - coc_get_ranking_builderbase_players, 16
 - coc_get_ranking_capitals, 17
 - coc_get_ranking_clans, 18
 - coc_get_ranking_players, 19
 - coc_get_ranking_versus_clans, 20
 - coc_get_ranking_versus_players, 21
 - * **player**
 - coc_get_player, 14
- coc_get_builderbase_league, 2
coc_get_builderbase_leagues, 3
coc_get_capital_league, 4
- coc_get_capital_leagues, 5
coc_get_capital_raid_seasons, 5
coc_get_clan, 6
coc_get_clan_labels, 7
coc_get_clan_members, 8
coc_get_clan_search, 8
coc_get_goldpass, 10
coc_get_key (key), 25
coc_get_league, 10
coc_get_league_seaons, 12
coc_get_leagues, 11
coc_get_location, 12
coc_get_locations, 13
coc_get_player, 14
coc_get_player_labels, 15
coc_get_ranking_builderbase_clans, 15
coc_get_ranking_builderbase_players, 16
coc_get_ranking_capitals, 17
coc_get_ranking_clans, 18
coc_get_ranking_players, 19
coc_get_ranking_versus_clans, 20
coc_get_ranking_versus_players, 21
- coc_get_ranking_versus_players, 21
- coc_has_key (key), 25
coc_set_key (set_clash_key), 25
- get_clash_key (key), 25
has_clash_key (key), 25
- key, 25
set_clash_key, 25