

Package: redistmetrics (via r-universe)

October 3, 2026

Title Redistricting Metrics

Version 1.0.11

Date 2025-12-15

Description Reliable and flexible tools for scoring redistricting plans using common measures and metrics. These functions provide key direct access to tools useful for non-simulation analyses of redistricting plans, such as for measuring compactness or partisan fairness. Tools are designed to work with the 'redist' package seamlessly.

Depends R (>= 4.1.0)

Imports sf, Rcpp, vctrs, cli, foreach, doParallel, magrittr, dplyr, rlang, geos, wk, libgeos

Suggests rmarkdown, knitr, testthat (>= 3.0.0), ggplot2

LinkingTo Rcpp, RcppArmadillo, RcppThread, libgeos

License MIT + file LICENSE

Encoding UTF-8

LazyData true

SystemRequirements C++17

Roxygen list(markdown = TRUE)

URL <https://alarm-redist.org/redistmetrics/>,
<https://github.com/alarm-redist/redistmetrics>

BugReports <https://github.com/alarm-redist/redistmetrics/issues>

VignetteBuilder knitr

Config/testthat/edition 3

Config/roxygen2/version 8.0.0

Config/pak/sysreqs libabsl-dev cmake libgdal-dev gdal-bin libgeos-dev libssl-dev libproj-dev libsqlite3-dev libudunits2-dev

Repository <https://christopherkenny.r-universe.dev>

Date/Publication 2026-10-03 15:05:21 UTC

RemoteUrl <https://github.com/alarm-redis/redismetrics>

RemoteRef HEAD

RemoteSha f8f32ac5dc43a0d2d11d188e9dfd74b323173d61

Contents

by_plan	3
comp_bbox_reock	4
comp_bc	4
comp_box_reock	5
comp_ch	6
comp_components	7
comp_corners	7
comp_edges_rem	8
comp_fh	9
comp_frac_kept	10
comp_holes	11
comp_jagged	12
comp_kiwysi	12
comp_log_st	13
comp_lw	14
comp_polsby	15
comp_reock	16
comp_schwartz	17
comp_skew	18
comp_x_sym	19
comp_y_sym	20
compet_talisman	21
dist_euc	22
dist_ham	23
dist_info	23
dist_man	24
inc_pairs	25
list_fn	26
nh	26
nh_m	28
nh_map	29
nh_plans	31
part_bias	31
part_decl	32
part_decl_simple	33
part_dil_asym	34
part_dislocation	35
part_dseats	36
part_dvs	37
part_egap	37
part_egap_ep	38

part_lop_wins	39
part_mean_median	40
part_resp	41
part_rmd	42
part_sscd	43
part_tau_gap	44
prep_perims	45
seg_dissim	45
splits_admin	46
splits_count	47
splits_district_fuzzy	48
splits_multi	49
splits_sub_admin	49
splits_sub_count	50
splits_sub_total	51
splits_total	52
tally	52

Index	54
--------------	-----------

by_plan	<i>Shorten District by Plan vector</i>
---------	--

Description

If x is repeated for each district, it returns a plan level value. Otherwise it returns x.

Usage

```
by_plan(x, ndists)
```

Arguments

x	summary statistic at the district level
ndists	numeric. Number of districts. Estimated as the ged of the unique run length encodings if missing.

Value

x or plan level subset of x

Examples

```
by_plan(letters)
by_plan(rep(letters, each = 2))
```

comp_bbox_reock	<i>Calculate Bounding Box Reock Compactness</i>
-----------------	---

Description

Box reock is the ratio of the area of the district by the area of the minimum bounding box (of fixed rotation). Scores are bounded between 0 and 1, where 1 is most compact.

Usage

```
comp_bbox_reock(plans, shp, epsg = 3857, ncores = 1)
```

Arguments

plans	A <code>redist_plans</code> object or <code>plans_matrix</code> where each row indicates a district assignment and each column is a plan.
shp	A <code>redist_map</code> object, tibble, or data frame with an <code>sf</code> geometry column.
epsg	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
ncores	Integer number of cores to use. Default is 1.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

Examples

```
#' data(nh)
data(nh_m)
# For a single plan:
comp_bbox_reock(plans = nh$r_2020, shp = nh)

# Or many plans:
comp_bbox_reock(plans = nh_m[, 1:5], shp = nh)
```

comp_bc	<i>Calculate Boyce Clark Ratio</i>
---------	------------------------------------

Description

Calculate Boyce Clark Ratio

Usage

```
comp_bc(plans, shp, epsg = 3857, ncores = 1)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame with an sf geometry column.
epsg	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
ncores	Integer number of cores to use. Default is 1.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Boyce, R., & Clark, W. 1964. The Concept of Shape in Geography. Geographical Review, 54(4), 561-572.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
comp_bc(plans = nh$r_2020, shp = nh)

# Or many plans:

# slower, beware!
comp_bc(plans = nh_m[, 3:5], shp = nh)
```

comp_box_reock	<i>Calculate Box Reock Compactness</i>
----------------	--

Description

Box reock is the ratio of the area of the district by the area of the minimum bounding box (of any rotation). Scores are bounded between 0 and 1, where 1 is most compact.

Usage

```
comp_box_reock(plans, shp, epsg = 3857, ncores = 1)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame with an sf geometry column.
epsg	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
ncores	Integer number of cores to use. Default is 1.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

Examples

```
#' data(nh)
data(nh_m)
# For a single plan:
comp_box_reock(plans = nh$r_2020, shp = nh)

# Or many plans:

# slower, beware!
comp_box_reock(plans = nh_m[, 3:5], shp = nh)
```

comp_ch

Calculate Convex Hull Compactness

Description

Calculate Convex Hull Compactness

Usage

```
comp_ch(plans, shp, epsg = 3857, ncores = 1)
```

Arguments

plans	A <code>redist_plans</code> object or <code>plans_matrix</code> where each row indicates a district assignment and each column is a plan.
shp	A <code>redist_map</code> object, tibble, or data frame with an sf geometry column.
epsg	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
ncores	Integer number of cores to use. Default is 1.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
comp_ch(plans = nh$r_2020, shp = nh)

# Or many plans:
comp_ch(plans = nh_m[, 3:5], shp = nh)
```

comp_components	<i>Count District Components</i>
-----------------	----------------------------------

Description

Counts polygon components after uniting each district geometry. Holes are not counted as components.

Usage

```
comp_components(plans, shp, epsg = 3857, ncores = 1)
```

Arguments

- plans A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
- shp A redist_map object, tibble, or data frame with an sf geometry column.
- epsg Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
- ncores Integer number of cores to use. Default is 1.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

Examples

```
data(nh)
data(nh_m)
comp_components(plans = nh$r_2020, shp = nh)
comp_components(plans = nh_m[, 1:2], shp = nh)
```

comp_corners	<i>Count District Corners</i>
--------------	-------------------------------

Description

Counts significant exterior-boundary turns after scale-normalized topology-preserving simplification.

Usage

```
comp_corners(  
  plans,  
  shp,  
  epsg = 3857,  
  ncores = 1,  
  tolerance = 0.01,  
  corner_angle = 30  
)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame with an sf geometry column.
epsg	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
ncores	Integer number of cores to use. Default is 1.
tolerance	Simplification tolerance as a share of the equivalent-circle radius.
corner_angle	Minimum turning angle, in degrees, counted as a corner.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

Examples

```
data(nh)  
data(nh_m)  
comp_corners(plans = nh$r_2020, shp = nh)  
comp_corners(plans = nh_m[, 1:2], shp = nh)
```

comp_edges_rem	<i>Calculate Edges Removed Compactness</i>
----------------	--

Description

Calculate Edges Removed Compactness

Usage

```
comp_edges_rem(plans, shp, adj)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame with an sf geometry column.
adj	Zero-indexed adjacency list. Not required if a redist_map is supplied for shp.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Matthew P. Dube and Jesse Tyler Clark. 2016. Beyond the circle: Measuring district compactness using graph theory. In Annual Meeting of the Northeastern Political Science Association

Examples

```
data(nh)
data(nh_m)
# For a single plan:
comp_edges_rem(plans = nh$r_2020, shp = nh, nh$adj)

# Or many plans:
comp_edges_rem(plans = nh_m[, 3:5], shp = nh, nh$adj)
```

comp_fh

Calculate Fryer Holden Compactness

Description

Calculate Fryer Holden Compactness

Usage

```
comp_fh(plans, shp, total_pop, epsg = 3857, ncores = 1)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame with an sf geometry column.
total_pop	A numeric vector with the population for every observation.
epsg	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
ncores	TRUE

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Fryer R, Holden R. 2011. Measuring the Compactness of Political Districting Plans. *Journal of Law and Economics*.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
comp_fh(plans = nh$r_2020, shp = nh, total_pop = pop)

# Or many plans:
comp_fh(plans = nh_m[, 3:5], shp = nh, pop)
```

comp_frac_kept

Calculate Fraction Kept Compactness

Description

Calculate Fraction Kept Compactness

Usage

```
comp_frac_kept(plans, shp, adj)
```

Arguments

plans	A <code>redist_plans</code> object or <code>plans_matrix</code> where each row indicates a district assignment and each column is a plan.
shp	A <code>redist_map</code> object, tibble, or data frame with an <code>sf</code> geometry column.
adj	Zero-indexed adjacency list. Not required if a <code>redist_map</code> is supplied for <code>shp</code> .

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Matthew P. Dube and Jesse Tyler Clark. 2016. Beyond the circle: Measuring district compactness using graph theory. In Annual Meeting of the Northeastern Political Science Association

Examples

```
data(nh)
data(nh_m)
# For a single plan:
comp_frac_kept(plans = nh$r_2020, shp = nh, nh$adj)

# Or many plans:
comp_frac_kept(plans = nh_m[, 3:5], shp = nh, nh$adj)
```

comp_holes	<i>Count District Holes</i>
------------	-----------------------------

Description

Counts interior rings after uniting each district geometry.

Usage

```
comp_holes(plans, shp, epsg = 3857, ncores = 1)
```

Arguments

plans	A <code>redist_plans</code> object or <code>plans_matrix</code> where each row indicates a district assignment and each column is a plan.
shp	A <code>redist_map</code> object, tibble, or data frame with an <code>sf</code> geometry column.
epsg	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
ncores	Integer number of cores to use. Default is 1.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

Examples

```
data(nh)
data(nh_m)
comp_holes(plans = nh$r_2020, shp = nh)
comp_holes(plans = nh_m[, 1:2], shp = nh)
```

comp_jagged	<i>Calculate Boundary Jaggedness</i>
-------------	--------------------------------------

Description

Counts simplified exterior boundary segments per equivalent-circle circumference. Larger values indicate more boundary segment changes for the district's size.

Usage

```
comp_jagged(plans, shp, epsg = 3857, ncores = 1, tolerance = 0.01)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame with an sf geometry column.
epsg	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
ncores	Integer number of cores to use. Default is 1.
tolerance	Simplification tolerance as a share of the equivalent-circle radius.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

Examples

```
data(nh)
data(nh_m)
comp_jagged(plans = nh$r_2020, shp = nh)
comp_jagged(plans = nh_m[, 1:2], shp = nh)
```

comp_kiwysi	<i>Calculate KIWSI Compactness</i>
-------------	------------------------------------

Description

Predicts the Kaufman, King, and Komisarchik "know it when you see it" compactness score by combining 14 redistmetrics compactness measures in a linear model. Scores are bounded between 0 and 100, where 0 is least compact and 100 is most compact.

Usage

```
comp_kiwysi(plans, shp, epsg = 3857, ncores = 1, return_all = FALSE, ...)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame with an sf geometry column.
epsg	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
ncores	Integer number of cores to use. Default is 1.
return_all	If TRUE, return a tibble containing the score and all features used by the model.
...	Precomputed feature vectors. These are tidy-evaluated in shp. Use the corresponding function name, such as comp_polsby = polsby.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Aaron Kaufman, Gary King, and Mayya Komisarchik. 2021. How to Measure Legislative District Compactness If You Only Know it When You See It. American Journal of Political Science. 65, 3. Pp. 533-550.

Examples

```
data(nh)
comp_kiwyisi(plans = nh$r_2020, shp = nh)
```

comp_log_st	<i>Calculate Log Spanning Tree Compactness</i>
-------------	--

Description

Calculate Log Spanning Tree Compactness

Usage

```
comp_log_st(plans, shp, counties = NULL, adj)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame with an sf geometry column.
counties	column name in shp containing counties
adj	Zero-indexed adjacency list. Not required if a redist_map is supplied for shp.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Cory McCartan and Kosuke Imai. 2020. Sequential Monte Carlo for Sampling Balanced and Compact Redistricting Plans.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
comp_log_st(plans = nh$r_2020, shp = nh, counties = county, adj = nh$adj)

# Or many plans:
comp_log_st(plans = nh_m[, 3:5], shp = nh, counties = county, adj = nh$adj)
```

comp_lw

Calculate Length Width Compactness

Description

Calculate Length Width Compactness

Usage

```
comp_lw(plans, shp, epsg = 3857, ncores = 1)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame with an sf geometry column.
epsg	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
ncores	Integer number of cores to use. Default is 1.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Harris, Curtis C. 1964. “A scientific method of districting”. Behavioral Science 3(9), 219–225.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
comp_lw(plans = nh$r_2020, shp = nh)

# Or many plans:

# slower, beware!
comp_lw(plans = nh_m[, 3:5], shp = nh)
```

comp_polsby

*Calculate Polsby Popper Compactness***Description**

Calculate Polsby Popper Compactness

Usage

```
comp_polsby(
  plans,
  shp,
  use_Rcpp,
  perim_path,
  perim_df,
  epsg = 3857,
  ncores = 1
)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame with an sf geometry column.
use_Rcpp	If TRUE (the default for more than 8 plans), precompute boundaries shared by each pair of units and use them to quickly compute the compactness score.
perim_path	Path to perimeter tibble saved by prep_perims()
perim_df	Tibble of perimeters from prep_perims()
epsg	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
ncores	Integer number of cores to use. Default is 1.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

- Cox, E. 1927. A Method of Assigning Numerical and Percentage Values to the Degree of Roundness of Sand Grains. *Journal of Paleontology*, 1(3), 179-183.
- Polsby, Daniel D., and Robert D. Popper. 1991. "The Third Criterion: Compactness as a procedural safeguard against partisan gerrymandering." *Yale Law & Policy Review* 9 (2): 301–353.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
comp_polsby(plans = nh$r_2020, shp = nh)

# Or many plans:
comp_polsby(plans = nh_m[, 3:5], shp = nh)
```

comp_reock	<i>Calculate Reock Compactness</i>
------------	------------------------------------

Description

Calculate Reock Compactness

Usage

```
comp_reock(plans, shp, epsg = 3857, ncores = 1)
```

Arguments

plans	A <code>redist_plans</code> object or <code>plans_matrix</code> where each row indicates a district assignment and each column is a plan.
shp	A <code>redist_map</code> object, tibble, or data frame with an <code>sf</code> geometry column.
epsg	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
ncores	Integer number of cores to use. Default is 1.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

- Reock, E. 1961. A Note: Measuring Compactness as a Requirement of Legislative Apportionment. *Midwest Journal of Political Science*, 5(1), 70-74.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
comp_reock(plans = nh$r_2020, shp = nh)

# Or many plans:
comp_reock(plans = nh_m[, 3:5], shp = nh)
```

comp_schwartz	<i>Calculate Schwartzberg Compactness</i>
---------------	---

Description

Calculate Schwartzberg Compactness

Usage

```
comp_schwartz(
  plans,
  shp,
  use_Rcpp,
  perim_path,
  perim_df,
  epsg = 3857,
  ncores = 1
)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame with an sf geometry column.
use_Rcpp	Logical. Use Rcpp?
perim_path	path to perimeter tibble saved by prep_perims()
perim_df	tibble of perimeters from prep_perims()
epsg	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
ncores	Integer number of cores to use. Default is 1.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Schwartzberg, Joseph E. 1966. Reapportionment, Gerrymanders, and the Notion of Compactness. Minnesota Law Review. 1701.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
comp_schwartz(plans = nh$r_2020, shp = nh)

# Or many plans:
comp_schwartz(plans = nh_m[, 3:5], shp = nh)
```

comp_skew

Calculate Skew Compactness

Description

Skew is defined as the ratio of the radii of the largest inscribed circle with the smallest bounding circle. Scores are bounded between 0 and 1, where 1 is most compact.

Usage

```
comp_skew(plans, shp, epsg = 3857, ncores = 1)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame with an sf geometry column.
epsg	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
ncores	Integer number of cores to use. Default is 1.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

S.N. Schumm. 1963. Sinuosity of alluvial rivers on the Great Plains. Bulletin of the Geological Society of America, 74. 1089-1100.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
comp_skew(plans = nh$r_2020, shp = nh)

# Or many plans:

# slower, beware!
comp_skew(plans = nh_m[, 3:5], shp = nh)
```

comp_x_sym

Calculate X Symmetry Compactness

Description

X symmetry is the overlapping area of a shape and its projection over the x-axis.

Usage

```
comp_x_sym(plans, shp, epsg = 3857, ncores = 1)
```

Arguments

plans	A <code>redist_plans</code> object or <code>plans_matrix</code> where each row indicates a district assignment and each column is a plan.
shp	A <code>redist_map</code> object, tibble, or data frame with an <code>sf</code> geometry column.
epsg	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
ncores	Integer number of cores to use. Default is 1.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Aaron Kaufman, Gary King, and Mayya Komisarchik. 2021. How to Measure Legislative District Compactness If You Only Know it When You See It. *American Journal of Political Science*. 65, 3. Pp. 533-550.

Examples

```
#' data(nh)
data(nh_m)
# For a single plan:
comp_x_sym(plans = nh$r_2020, shp = nh)

# Or many plans:

# slower, beware!
comp_x_sym(plans = nh_m[, 3:5], shp = nh)
```

comp_y_sym

Calculate Y Symmetry Compactness

Description

Y symmetry is the overlapping area of a shape and its projection over the y-axis.

Usage

```
comp_y_sym(plans, shp, epsg = 3857, ncores = 1)
```

Arguments

plans	A <code>redist_plans</code> object or <code>plans_matrix</code> where each row indicates a district assignment and each column is a plan.
shp	A <code>redist_map</code> object, tibble, or data frame with an <code>sf</code> geometry column.
epsg	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
ncores	Integer number of cores to use. Default is 1.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Aaron Kaufman, Gary King, and Mayya Komisarchik. 2021. How to Measure Legislative District Compactness If You Only Know it When You See It. *American Journal of Political Science*. 65, 3. Pp. 533-550.

Examples

```
#' data(nh)
data(nh_m)
# For a single plan:
comp_y_sym(plans = nh$r_2020, shp = nh)

# Or many plans:

# slower, beware!
comp_y_sym(plans = nh_m[, 3:5], shp = nh)
```

compet_talisman

*Compute Talismanic Redistricting Competitiveness Metric***Description**

Compute Talismanic Redistricting Competitiveness Metric

Usage

```
compet_talisman(plans, shp, rvote, dvote, alpha = 1, beta = 1)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame containing other columns.
rvote	Unquoted name of column in shp with group population.
dvote	Unquoted name of column in shp with total population.
alpha	Numeric scaling value
beta	Numeric scaling value

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Wendy K. Tam Cho and Yan Y. Liu Toward a Talismanic Redistricting Tool. Election Law Journal. 15, 4. Pp. 351-366.

Examples

```

data(nh)
data(nh_m)
# For a single plan:
compet_talisman(plans = nh$r_2020, shp = nh, rvote = nrv, dvote = ndv)

# Or many plans:
compet_talisman(plans = nh_m[, 3:5], shp = nh, rvote = nrv, dvote = ndv)

```

dist_euc

Calculate Euclidean Distances

Description

Calculate Euclidean Distances

Usage

```
dist_euc(plans, ncores = 1)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
ncores	Integer number of cores to use. Default is 1.

Value

matrix of plan distances

Examples

```

data(nh)
data(nh_m)
# For a single plan (distance is trivial, 0):
dist_euc(plans = nh$r_2020)

# Or many plans:
dist_euc(plans = nh_m[, 3:5])

```

dist_ham	<i>Calculate Hamming Distances</i>
----------	------------------------------------

Description

Calculate Hamming Distances

Usage

```
dist_ham(plans, ncores = 1)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
ncores	Integer number of cores to use. Default is 1.

Value

matrix of plan distances

Examples

```
data(nh)
data(nh_m)
# For a single plan (distance is trivial, 0):
dist_ham(plans = nh$r_2020)

# Or many plans:
dist_ham(plans = nh_m[, 3:5])
```

dist_info	<i>Calculate Variation of Information Distances</i>
-----------	---

Description

Calculate Variation of Information Distances

Usage

```
dist_info(plans, shp, total_pop, ncores = 1)
```

Arguments

plans	A <code>redist_plans</code> object or <code>plans_matrix</code> where each row indicates a district assignment and each column is a plan.
shp	A <code>redist_map</code> object, tibble, or data frame containing other columns.
total_pop	Unquoted name of column in <code>shp</code> with total population.
ncores	Integer number of cores to use. Default is 1.

Value

matrix of plan distances

Examples

```
data(nh)
data(nh_m)
# For a single plan (distance is trivial, 0):
dist_info(plans = nh$r_2020, shp = nh, total_pop = pop)

# Or many plans:
dist_info(plans = nh_m[, 3:5], shp = nh, total_pop = pop)
```

<code>dist_man</code>	<i>Calculate Manhattan Distances</i>
-----------------------	--------------------------------------

Description

Calculate Manhattan Distances

Usage

```
dist_man(plans, ncores = 1)
```

Arguments

plans	A <code>redist_plans</code> object or <code>plans_matrix</code> where each row indicates a district assignment and each column is a plan.
ncores	Integer number of cores to use. Default is 1.

Value

matrix of plan distances

Examples

```
data(nh)
data(nh_m)
# For a single plan (distance is trivial, 0):
dist_man(plans = nh$r_2020)

# Or many plans:
dist_man(plans = nh_m[, 3:5])
```

inc_pairs	<i>Count Incumbent Pairings</i>
-----------	---------------------------------

Description

Count the number of incumbents paired with at least one other incumbent.

Usage

```
inc_pairs(plans, shp, inc)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame containing other columns.
inc	Unquoted name of logical column in shp indicating where incumbents live.

Value

vector of number of incumbents paired

Examples

```
data(nh)
data(nh_m)
# Use incumbent data:
fake_inc <- rep(FALSE, nrow(nh))
fake_inc[3:4] <- TRUE

# For a single plan:
inc_pairs(plans = nh$r_2020, shp = nh, inc = fake_inc)

# Or many plans:
inc_pairs(plans = nh_m[, 3:5], shp = nh, inc = fake_inc)
```

list_fn	<i>Return Functions Matching a Prefix</i>
---------	---

Description

This package uses prefixes for each function that correspond to the type of measure. This function returns the functions

Usage

```
list_fn(prefix)
```

Arguments

prefix character prefix of functions to return

Value

character vector of functions

Examples

```
list_fn('part_')
```

nh	<i>New Hampshire Election and Demographic Data</i>
----	--

Description

This data set contains demographic, election, and geographic information for the 326 voting tabulation districts in New Hampshire in 2020.

Usage

```
data("nh")
```

Format

A tibble with 326 rows and 45 columns

- GEOID20: 2020 VTD GEOID
- state: state name
- county: county name
- vtd: VTD portion of GEOID
- pop: total population

- pop_hisp: Hispanic population
- pop_white: White, not Hispanic population
- pop_black: Black, not Hispanic population
- pop_aian: American Indian and Alaska Native, not Hispanic population
- pop_asian: Asian, not Hispanic population
- pop_nhpi: Native Hawaiian and Pacific Islander, not Hispanic population
- pop_other: other race, not Hispanic population
- pop_two: multi-race, not Hispanic population
- vap: total voting-age population
- vap_hisp: Hispanic voting-age population
- vap_white: White, not Hispanic voting-age population
- vap_black: Black, not Hispanic voting-age population
- vap_aian: American Indian and Alaska Native, not Hispanic voting-age population
- vap_asian: Asian, not Hispanic voting-age population
- vap_nhpi: Native Hawaiian and Pacific Islander, not Hispanic voting-age population
- vap_other: other race, not Hispanic voting-age population
- vap_two: multi-race, not Hispanic voting-age population
- pre_16_rep_tru: Votes for Republican president 2016
- pre_16_dem_cli: Votes for Democratic president 2016
- uss_16_rep_ayo: Votes for Republican senate 2016
- uss_16_dem_has: Votes for Democratic senate 2016
- gov_16_rep_sun: Votes for Republican governor 2016
- gov_16_dem_van: Votes for Democratic governor 2016
- gov_18_rep_sun: Votes for Republican governor 2018
- gov_18_dem_kel: Votes for Democratic governor 2018
- pre_20_dem_bid: Votes for Democratic president 2020
- pre_20_rep_tru: Votes for Republican president 2020
- uss_20_dem_sha: Votes for Democratic senate 2020
- uss_20_rep_mes: Votes for Republican senate 2020
- gov_20_dem_fel: Votes for Democratic governor 2020
- gov_20_rep_sun: Votes for Republican governor 2020
- arv_16: Average Republican vote 2016
- adv_16: Average Democratic vote 2016
- arv_18: Average Republican vote 2018
- adv_18: Average Democratic vote 2018
- arv_20: Average Republican vote 2020
- adv_20: Average Democratic vote 2020

- nrv: Normal Republican vote
- ndv: Normal Democratic vote
- geometry: sf geometry, simplified for size using rmapshaper
- r_2020: Republican proposed plan for 2020 Congressional districts
- d_2020: Democratic proposed plan for 2020 Congressional districts
- adj: zero-indexed adjacency graph

References

Voting and Election Science Team, 2020, "2020 Precinct-Level Election Results", <https://doi.org/10.7910/DVN/K7760H>, Harvard Dataverse, V23

Voting and Election Science Team, 2018, "2016 Precinct-Level Election Results", <https://doi.org/10.7910/DVN/NH5S2I>, Harvard Dataverse, V71

Voting and Election Science Team, 2019, "2018 Precinct-Level Election Results", <https://doi.org/10.7910/DVN/UBKYRU>, Harvard Dataverse, V48

Kenny & McCartan (2021, Aug. 10). ALARM Project: 2020 Redistricting Data Files. Retrieved from <https://github.com/alarm-redist/census-2020/>

Examples

```
data(nh)
```

nh_m

Redistricting Plans for New Hampshire as matrix

Description

This data set contains two reference plans (d_2020 and r_2020) and 50 simulated plans for New Hampshire, based on 2020 demographics, simulated at a population tolerance of 0.05%.

Usage

```
data("nh_m")
```

Format

A matrix with 52 columns and 326 rows where each column is a plan

Examples

```
data(nh_m)
```

nh_map

*New Hampshire Election and Demographic Data as a redist_map***Description**

This data set contains demographic, election, and geographic information for the 326 voting tabulation districts in New Hampshire in 2020.

Usage

```
data("nh_map")
```

Format

A redist_map with 326 rows and 45 columns

- GEOID20: 2020 VTD GEOID
- state: state name
- county: county name
- vtd: VTD portion of GEOID
- pop: total population
- pop_hisp: Hispanic population
- pop_white: White, not Hispanic population
- pop_black: Black, not Hispanic population
- pop_aian: American Indian and Alaska Native, not Hispanic population
- pop_asian: Asian, not Hispanic population
- pop_nhpi: Native Hawaiian and Pacific Islander, not Hispanic population
- pop_other: other race, not Hispanic population
- pop_two: multi-race, not Hispanic population
- vap: total voting-age population
- vap_hisp: Hispanic voting-age population
- vap_white: White, not Hispanic voting-age population
- vap_black: Black, not Hispanic voting-age population
- vap_aian: American Indian and Alaska Native, not Hispanic voting-age population
- vap_asian: Asian, not Hispanic voting-age population
- vap_nhpi: Native Hawaiian and Pacific Islander, not Hispanic voting-age population
- vap_other: other race, not Hispanic voting-age population
- vap_two: multi-race, not Hispanic voting-age population
- pre_16_rep_tru: Votes for Republican president 2016
- pre_16_dem_cli: Votes for Democratic president 2016

- `uss_16_rep_ayo`: Votes for Republican senate 2016
- `uss_16_dem_has`: Votes for Democratic senate 2016
- `gov_16_rep_sun`: Votes for Republican governor 2016
- `gov_16_dem_van`: Votes for Democratic governor 2016
- `gov_18_rep_sun`: Votes for Republican governor 2018
- `gov_18_dem_kel`: Votes for Democratic governor 2018
- `pre_20_dem_bid`: Votes for Democratic president 2020
- `pre_20_rep_tru`: Votes for Republican president 2020
- `uss_20_dem_sha`: Votes for Democratic senate 2020
- `uss_20_rep_mes`: Votes for Republican senate 2020
- `gov_20_dem_fel`: Votes for Democratic governor 2020
- `gov_20_rep_sun`: Votes for Republican governor 2020
- `arv_16`: Average Republican vote 2016
- `adv_16`: Average Democratic vote 2016
- `arv_18`: Average Republican vote 2018
- `adv_18`: Average Democratic vote 2018
- `arv_20`: Average Republican vote 2020
- `adv_20`: Average Democratic vote 2020
- `nrv`: Normal Republican vote
- `ndv`: Normal Democratic vote
- `r_2020`: Republican proposed plan for 2020 Congressional districts
- `d_2020`: Democratic proposed plan for 2020 Congressional districts
- `adj`: zero-indexed adjacency graph
- `geometry`: sf geometry, simplified for size using rmapshaper

References

- Voting and Election Science Team, 2020, "2020 Precinct-Level Election Results", <https://doi.org/10.7910/DVN/K7760H>, Harvard Dataverse, V23
- Voting and Election Science Team, 2018, "2016 Precinct-Level Election Results", <https://doi.org/10.7910/DVN/NH5S2I>, Harvard Dataverse, V71
- Voting and Election Science Team, 2019, "2018 Precinct-Level Election Results", <https://doi.org/10.7910/DVN/UBKYRU>, Harvard Dataverse, V48
- Kenny & McCartan (2021, Aug. 10). ALARM Project: 2020 Redistricting Data Files. Retrieved from <https://github.com/alarm-redist/census-2020/>

Examples

```
data(nh_map)
```

nh_plans

*Redistricting Plans for New Hampshire as redist_plans***Description**

This data set contains two reference plans (d_2020 and r_2020) and 50 simulated plans for New Hampshire, based on 2020 demographics, simulated at a population tolerance of 0.05%.

Usage

```
data("nh_plans")
```

Format

A redist_plans with 104 rows and 3 columns

- draw: factor identifying the reference plans (d_2020 and r_2020) and 50 simulated plans
- district: district number (1 or 2)
- total_pop: total population in the district

Examples

```
data(nh_plans)
```

part_bias

*Calculate Partisan Bias***Description**

Calculate Partisan Bias

Usage

```
part_bias(plans, shp, dvote, rvote, v = 0.5)
```

Arguments

- | | |
|-------|---|
| plans | A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan. |
| shp | A redist_map object, tibble, or data frame containing other columns. |
| dvote | Unquoted name of column in shp with total population. |
| rvote | Unquoted name of column in shp with group population. |
| v | vote share to calculate bias at. Numeric. Default is 0.5. |

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Jonathan N. Katz, Gary King, and Elizabeth Rosenblatt. 2020. Theoretical Foundations and Empirical Evaluations of Partisan Fairness in District-Based Democracies. *American Political Science Review*, 114, 1, Pp. 164-178.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
part_bias(plans = nh$r_2020, shp = nh, rvote = nrv, dvote = ndv)

# Or many plans:
part_bias(plans = nh_m[, 3:5], shp = nh, rvote = nrv, dvote = ndv)
```

part_decl

Calculate Declination

Description

Calculate Declination

Usage

```
part_decl(plans, shp, dvote, rvote, normalize = TRUE, adjust = TRUE)
```

Arguments

plans	A <code>redist_plans</code> object or <code>plans_matrix</code> where each row indicates a district assignment and each column is a plan.
shp	A <code>redist_map</code> object, tibble, or data frame containing other columns.
dvote	Unquoted name of column in <code>shp</code> with total population.
rvote	Unquoted name of column in <code>shp</code> with group population.
normalize	Default is TRUE Translate score to an angle?
adjust	Default is TRUE. Applies a correction to increase cross-size comparison.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Gregory S. Warrington. 2018. "Quantifying Gerrymandering Using the Vote Distribution." Election Law Journal: Rules, Politics, and Policy. Pp. 39-57.<http://doi.org/10.1089/elj.2017.0447>

Examples

```
data(nh)
data(nh_m)
# For a single plan:
part_decl(plans = nh$r_2020, shp = nh, rvote = nrv, dvote = ndv)

# Or many plans:
part_decl(plans = nh_m[, 3:5], shp = nh, rvote = nrv, dvote = ndv)
```

part_decl_simple	<i>Calculate Simplified Declination</i>
------------------	---

Description

Calculate Simplified Declination

Usage

```
part_decl_simple(plans, shp, dvote, rvote)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame containing other columns.
dvote	Unquoted name of column in shp with total population.
rvote	Unquoted name of column in shp with group population.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Jonathan N. Katz, Gary King, and Elizabeth Rosenblatt. 2020. Theoretical Foundations and Empirical Evaluations of Partisan Fairness in District-Based Democracies. American Political Science Review, 114, 1, Pp. 164-178.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
part_decl_simple(plans = nh$r_2020, shp = nh, rvote = nrv, dvote = ndv)

# Or many plans:
part_decl_simple(plans = nh_m[, 3:5], shp = nh, rvote = nrv, dvote = ndv)
```

part_dil_asym	<i>Calculate Dilution Asymmetry</i>
---------------	-------------------------------------

Description

Calculate Dilution Asymmetry

Usage

```
part_dil_asym(plans, shp, dvote, rvote)
```

Arguments

- plans A `redist_plans` object or `plans_matrix` where each row indicates a district assignment and each column is a plan.
- shp A `redist_map` object, tibble, or data frame containing other columns.
- dvote Unquoted name of column in `shp` with total population.
- rvote Unquoted name of column in `shp` with group population.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Sanford C. Gordon and Sidak Yntiso. 2024. Base Rate Neglect and the Diagnosis of Partisan Gerrymanders. *Election Law Journal: Rules, Politics, and Policy*. doi:10.1089/elj.2023.0005.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
part_dil_asym(plans = nh$r_2020, shp = nh, rvote = nrv, dvote = ndv)

# Or many plans:
part_dil_asym(plans = nh_m[, 3:5], shp = nh, rvote = nrv, dvote = ndv)
```

part_dislocation	<i>Calculate Partisan Dislocation</i>
------------------	---------------------------------------

Description

Calculate Partisan Dislocation

Usage

```
part_dislocation(
  plans,
  shp,
  dvote,
  rvote,
  total_pop = dvote + rvote,
  epsg = 3857,
  by_precinct = FALSE,
  signed = TRUE
)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame with an sf geometry column.
dvote	Unquoted name of column in shp with total population.
rvote	Unquoted name of column in shp with group population.
total_pop	Unquoted name of column in shp with total population.
epsg	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
by_precinct	Defaults to FALSE, returning district-level values.
signed	Defaults to TRUE. Should the output for district-level values be signed? Setting to TRUE returns precinct-level values.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

DeFord, D. R., Eubank, N., & Rodden, J. (2022). Partisan dislocation: A precinct-level measure of representation and gerrymandering. *Political Analysis*, 30(3), 403-425.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
part_dislocation(plans = nh$r_2020, shp = nh, rvote = nrv, dvote = ndv)

# Or many plans:
part_dislocation(plans = nh_m[, 3:5], shp = nh, rvote = nrv, dvote = ndv)
```

part_dseats	<i>Calculate Democratic Seats</i>
-------------	-----------------------------------

Description

Calculate Democratic Seats

Usage

```
part_dseats(plans, shp, dvote, rvote)
```

Arguments

- plans A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
- shp A redist_map object, tibble, or data frame containing other columns.
- dvote Unquoted name of column in shp with total population.
- rvote Unquoted name of column in shp with group population.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
part_dseats(plans = nh$r_2020, shp = nh, rvote = nrv, dvote = ndv)

# Or many plans:
part_dseats(plans = nh_m[, 3:5], shp = nh, rvote = nrv, dvote = ndv)
```

part_dvs	<i>Calculate Democratic Vote Share</i>
----------	--

Description

Calculate Democratic Vote Share

Usage

```
part_dvs(plans, shp, dvote, rvote)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame containing other columns.
dvote	Unquoted name of column in shp with total population.
rvote	Unquoted name of column in shp with group population.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
part_dvs(plans = nh$r_2020, shp = nh, rvote = nrv, dvote = ndv)

# Or many plans:
part_dvs(plans = nh_m[, 3:5], shp = nh, rvote = nrv, dvote = ndv)
```

part_egap	<i>Calculate Efficiency Gap</i>
-----------	---------------------------------

Description

Calculate Efficiency Gap

Usage

```
part_egap(plans, shp, dvote, rvote)
```

Arguments

plans	A <code>redist_plans</code> object or <code>plans_matrix</code> where each row indicates a district assignment and each column is a plan.
shp	A <code>redist_map</code> object, tibble, or data frame containing other columns.
dvote	Unquoted name of column in <code>shp</code> with total population.
rvote	Unquoted name of column in <code>shp</code> with group population.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Nicholas O. Stephanopoulos. 2015. Partisan Gerrymandering and the Efficiency Gap. *The University of Chicago Law Review*, 82, Pp. 831-900.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
part_egap(plans = nh$r_2020, shp = nh, rvote = nrv, dvote = ndv)

# Or many plans:
part_egap(plans = nh_m[, 3:5], shp = nh, rvote = nrv, dvote = ndv)
```

part_egap_ep

Calculate Efficiency Gap (Equal Population Assumption)

Description

Calculate Efficiency Gap (Equal Population Assumption)

Usage

```
part_egap_ep(plans, shp, dvote, rvote)
```

Arguments

plans	A <code>redist_plans</code> object or <code>plans_matrix</code> where each row indicates a district assignment and each column is a plan.
shp	A <code>redist_map</code> object, tibble, or data frame containing other columns.
dvote	Unquoted name of column in <code>shp</code> with total population.
rvote	Unquoted name of column in <code>shp</code> with group population.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Nicholas O. Stephanopoulos. 2015. Partisan Gerrymandering and the Efficiency Gap. The University of Chicago Law Review, 82, Pp. 831-900.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
part_egap_ep(plans = nh$r_2020, shp = nh, rvote = nrv, dvote = ndv)

# Or many plans:
part_egap_ep(plans = nh_m[, 3:5], shp = nh, rvote = nrv, dvote = ndv)
```

part_lop_wins	<i>Calculate Lopsided Wins</i>
---------------	--------------------------------

Description

Calculate Lopsided Wins

Usage

```
part_lop_wins(plans, shp, dvote, rvote)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame containing other columns.
dvote	Unquoted name of column in shp with total population.
rvote	Unquoted name of column in shp with group population.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Samuel S.-H. Wang. 2016. "Three Tests for Practical Evaluation of Partisan Gerrymandering." Stanford Law Review, 68, Pp. 1263 - 1321.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
part_lop_wins(plans = nh$r_2020, shp = nh, rvote = nrv, dvote = ndv)

# Or many plans:
part_lop_wins(plans = nh_m[, 3:5], shp = nh, rvote = nrv, dvote = ndv)
```

part_mean_median	<i>Calculate Mean Median Score</i>
------------------	------------------------------------

Description

Calculate Mean Median Score

Usage

```
part_mean_median(plans, shp, dvote, rvote)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame containing other columns.
dvote	Unquoted name of column in shp with total population.
rvote	Unquoted name of column in shp with group population.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Michael D. McDonald and Robin E. Best. 2015. Unfair Partisan Gerrymanders in Politics and Law: A Diagnostic Applied to Six Cases. Election Law Journal: Rules, Politics, and Policy. 14. 4. Pp. 312-330.

Examples

```
data(nh)
data(nh_m)
# zero for the two district case:
# For a single plan:
part_mean_median(plans = nh$r_2020, shp = nh, rvote = nrv, dvote = ndv)

# Or many plans:
```

```
part_mean_median(plans = nh_m[, 3:5], shp = nh, rvote = nrv, dvote = ndv)
```

part_resp

Calculate Responsiveness

Description

Calculate Responsiveness

Usage

```
part_resp(plans, shp, dvote, rvote, v = 0.5, bandwidth = 0.01)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame containing other columns.
dvote	Unquoted name of column in shp with total population.
rvote	Unquoted name of column in shp with group population.
v	vote share to calculate bias at. Numeric. Default is 0.5.
bandwidth	Defaults to 0.01. A value between 0 and 1 for the step size to estimate the slope.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Jonathan N. Katz, Gary King, and Elizabeth Rosenblatt. 2020. Theoretical Foundations and Empirical Evaluations of Partisan Fairness in District-Based Democracies. *American Political Science Review*, 114, 1, Pp. 164-178.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
part_resp(plans = nh$r_2020, shp = nh, rvote = nrv, dvote = ndv)

# Or many plans:
part_resp(plans = nh_m[, 3:5], shp = nh, rvote = nrv, dvote = ndv)
```

part_rmd

*Calculate Ranked Marginal Deviation***Description**

Calculate Ranked Marginal Deviation

Usage

```
part_rmd(plans, shp, dvote, rvote)
```

Arguments

plans	A <code>redist_plans</code> object or <code>plans_matrix</code> where each row indicates a district assignment and each column is a plan.
shp	A <code>redist_map</code> object, tibble, or data frame containing other columns.
dvote	Unquoted name of column in <code>shp</code> with total population.
rvote	Unquoted name of column in <code>shp</code> with group population.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Gregory Herschlag, Han Sung Kang, Justin Luo, Christy Vaughn Graves, Sachet Bangia, Robert Ravier & Jonathan C. Mattingly (2020) Quantifying Gerrymandering in North Carolina, *Statistics and Public Policy*, 7:1, 30-38, DOI: 10.1080/2330443X.2020.1796400

Examples

```
data(nh)
data(nh_m)
# For a single plan:
part_rmd(plans = nh$r_2020, shp = nh, rvote = nrv, dvote = ndv)

# Or many plans:
part_rmd(plans = nh_m[, 3:5], shp = nh, rvote = nrv, dvote = ndv)
```

`part_sscd`*Calculate Smoothed Seat Count Deviation*

Description

Calculate Smoothed Seat Count Deviation

Usage

```
part_sscd(plans, shp, dvote, rvote)
```

Arguments

<code>plans</code>	A <code>redist_plans</code> object or <code>plans_matrix</code> where each row indicates a district assignment and each column is a plan.
<code>shp</code>	A <code>redist_map</code> object, tibble, or data frame containing other columns.
<code>dvote</code>	Unquoted name of column in <code>shp</code> with total population.
<code>rvote</code>	Unquoted name of column in <code>shp</code> with group population.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Gregory Herschlag, Han Sung Kang, Justin Luo, Christy Vaughn Graves, Sachet Bangia, Robert Ravier & Jonathan C. Mattingly (2020) Quantifying Gerrymandering in North Carolina, *Statistics and Public Policy*, 7:1, 30-38, DOI: 10.1080/2330443X.2020.1796400

Examples

```
data(nh)
data(nh_m)
# For a single plan:
part_sscd(plans = nh$r_2020, shp = nh, rvote = nrv, dvote = ndv)

# Or many plans:
part_sscd(plans = nh_m[, 3:5], shp = nh, rvote = nrv, dvote = ndv)
```

part_tau_gap

Calculate Tau Gap

Description

Calculate Tau Gap

Usage

```
part_tau_gap(plans, shp, dvote, rvote, tau = 1)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame containing other columns.
dvote	Unquoted name of column in shp with total population.
rvote	Unquoted name of column in shp with group population.
tau	A non-negative numeric for calculating Tau Gap. Defaults to 1.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Gregory S. Warrington. 2018. "Quantifying Gerrymandering Using the Vote Distribution." Election Law Journal: Rules, Politics, and Policy. Pp. 39-57.<http://doi.org/10.1089/elj.2017.0447>

Examples

```
data(nh)
data(nh_m)
# For a single plan:
part_tau_gap(plans = nh$r_2020, shp = nh, rvote = nrv, dvote = ndv)

# Or many plans:
part_tau_gap(plans = nh_m[, 3:5], shp = nh, rvote = nrv, dvote = ndv)
```

prep_perims	<i>Prep Polsby Popper Perimeter Tibble</i>
-------------	--

Description

Replaces `redist.prep.polsbypopper`

Usage

```
prep_perims(shp, epsg = 3857, perim_path, ncores = 1)
```

Arguments

<code>shp</code>	A <code>redist_map</code> object, tibble, or data frame with an sf geometry column.
<code>epsg</code>	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.
<code>perim_path</code>	A path to save an rds
<code>ncores</code>	Integer number of cores to use. Default is 1.

Value

tibble of perimeters and lengths

Examples

```
data(nh)
prep_perims(nh)
```

seg_dissim	<i>Compute Dissimilarity Index</i>
------------	------------------------------------

Description

Compute Dissimilarity Index

Usage

```
seg_dissim(plans, shp, group_pop, total_pop)
```

Arguments

<code>plans</code>	A <code>redist_plans</code> object or <code>plans_matrix</code> where each row indicates a district assignment and each column is a plan.
<code>shp</code>	A <code>redist_map</code> object, tibble, or data frame containing other columns.
<code>group_pop</code>	Unquoted name of column in <code>shp</code> with group population.
<code>total_pop</code>	Unquoted name of column in <code>shp</code> with total population.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

References

Douglas Massey and Nancy Denton. 1987. The Dimensions of Social Segregation. Social Forces.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
seg_dissim(plans = nh$r_2020, shp = nh, group_pop = vap_hisp, total_pop = vap)

# Or many plans:
seg_dissim(plans = nh_m[, 3:5], shp = nh, group_pop = vap_hisp, total_pop = vap)
```

splits_admin

Compute Number of Administrative Units Split

Description

Compute Number of Administrative Units Split

Usage

```
splits_admin(plans, shp, admin)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame containing other columns.
admin	Unquoted name of column in shp with numeric identifiers for administrative units.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
splits_admin(plans = nh$r_2020, shp = nh, admin = county)

# Or many plans:
splits_admin(plans = nh_m[, 3:5], shp = nh, admin = county)
```

splits_count*Count the Number of Splits in Each Administrative Unit*

Description

Tallies the number of unique administrative unit-districts. An unsplit administrative unit will return an entry of 1, while each additional administrative unit-district adds 1.

Usage

```
splits_count(plans, shp, admin)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame containing other columns.
admin	Unquoted name of column in shp with numeric identifiers for administrative units.

Value

numeric matrix

Examples

```
data(nh)
data(nh_m)
# For a single plan:
splits_count(plans = nh$r_2020, shp = nh, admin = county)

# Or many plans:
splits_count(plans = nh_m[, 3:5], shp = nh, admin = county)
```

splits_district_fuzzy *Fuzzy Splits by District (Experimental)*

Description

Not all relevant geographies nest neatly into Census blocks, including communities of interest or neighborhood. For these cases, this provides a tabulation by district of the number of splits. As some geographies can be split multiple times, the sum of these splits may not reflect the total number of splits.

Usage

```
splits_district_fuzzy(plans, shp, nbr, thresh = 0.01, epsg)
```

Arguments

plans	A <code>redist_plans</code> object or <code>plans_matrix</code> where each row indicates a district assignment and each column is a plan.
shp	A <code>redist_map</code> object, tibble, or data frame with an <code>sf</code> geometry column.
nbr	Geographic neighborhood, community, or other unit to check splits for.
thresh	Percent as decimal of an area to trim away. Default is .01, which is 1%.
epsg	Numeric EPSG code to use to project the shapefile, if needed. Default is 3857.

Details

Beware, this requires a `nbr` shape input and will be slower than checking splits in cases where administrative unit nests cleanly into the geographies represented by `shp`.

Value

numeric matrix

Examples

```
data(nh)
data(nh_m)

# toy example,
# suppose we care about the splits of the counties and they don't nest
nh_cty <- nh %>% dplyr::group_by(county) %>% dplyr::summarize()

# For a single plan:
splits_district_fuzzy(plans = nh$r_2020, shp = nh, nbr = nh_cty)

# Or many plans:
splits_district_fuzzy(plans = nh_m[, 3:5], shp = nh, nbr = nh_cty)
```

splits_multi	<i>Compute Number of Administrative Units Split More than Once</i>
--------------	--

Description

Compute Number of Administrative Units Split More than Once

Usage

```
splits_multi(plans, shp, admin)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame containing other columns.
admin	Unquoted name of column in shp with numeric identifiers for administrative units.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
splits_multi(plans = nh$r_2020, shp = nh, admin = county)

# Or many plans:
splits_multi(plans = nh_m[, 3:5], shp = nh, admin = county)
```

splits_sub_admin	<i>Compute Number of Sub-Administrative Units Split</i>
------------------	---

Description

Compute Number of Sub-Administrative Units Split

Usage

```
splits_sub_admin(plans, shp, sub_admin)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame containing other columns.
sub_admin	Unquoted name of column in shp with numeric identifiers for subsidiary administrative units.

Value

A numeric vector. Can be shaped into a district-by-plan matrix.

Examples

```
data(nh)
data(nh_m)
# For a single plan:
splits_sub_admin(plans = nh$r_2020, shp = nh, sub_admin = county)

# Or many plans:
splits_sub_admin(plans = nh_m[, 3:5], shp = nh, sub_admin = county)
```

splits_sub_count	<i>Count the Number of Splits in Each Sub-Administrative Unit</i>
------------------	---

Description

Tallies the number of unique sub-administrative unit-districts. An unsplit administrative unit will return an entry of 1, while each additional sub-administrative unit-district adds 1.

Usage

```
splits_sub_count(plans, shp, sub_admin)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame containing other columns.
sub_admin	Unquoted name of column in shp with numeric identifiers for subsidiary administrative units.

Value

numeric matrix

Examples

```
data(nh)
data(nh_m)
# For a single plan:
splits_sub_count(plans = nh$r_2020, shp = nh, sub_admin = county)

# Or many plans:
splits_sub_count(plans = nh_m[, 3:5], shp = nh, sub_admin = county)
```

splits_sub_total	<i>Count the Total Sub-Administrative Unit in Each Plan</i>
------------------	---

Description

Counts the total number of sub-administrative splits.

Usage

```
splits_sub_total(plans, shp, sub_admin)
```

Arguments

plans	A <code>redist_plans</code> object or <code>plans_matrix</code> where each row indicates a district assignment and each column is a plan.
shp	A <code>redist_map</code> object, tibble, or data frame containing other columns.
sub_admin	Unquoted name of column in <code>shp</code> with numeric identifiers for subsidiary administrative units.

Value

numeric matrix

Examples

```
data(nh)
data(nh_m)
# For a single plan:
splits_sub_total(plans = nh$r_2020, shp = nh, sub_admin = county)

# Or many plans:
splits_sub_total(plans = nh_m[, 3:5], shp = nh, sub_admin = county)
```

splits_total	<i>Count the Total Splits in Each Plan</i>
--------------	--

Description

Counts the total number of administrative splits.

Usage

```
splits_total(plans, shp, admin)
```

Arguments

plans	A redist_plans object or plans_matrix where each row indicates a district assignment and each column is a plan.
shp	A redist_map object, tibble, or data frame containing other columns.
admin	Unquoted name of column in shp with numeric identifiers for administrative units.

Value

numeric matrix

Examples

```
data(nh)
data(nh_m)
# For a single plan:
splits_total(plans = nh$r_2020, shp = nh, admin = county)

# Or many plans:
splits_total(plans = nh_m[, 3:5], shp = nh, admin = county)
```

tally	<i>Tally a Column by District</i>
-------	-----------------------------------

Description

Helper function to aggregate a vector by district. Can be used to calculate total population, group percentages, and more.

Usage

```
tally(plans, shp, x)
```

Arguments

plans	A <code>redist_plans</code> object or <code>plans_matrix</code> where each row indicates a district assignment and each column is a plan.
shp	A <code>redist_map</code> object, tibble, or data frame containing other columns.
x	The numeric vector to tally.

Value

A numeric vector with the tallies. Can be shaped into a district-by-plan matrix.

Examples

```
data(nh)
data(nh_m)
```

```
tally(nh_m, nh, pop) # total population
tally(nh_m, nh, vap_hisp) / tally(nh_m, nh, vap) # HVAP
```

Index

- * **compactness**
 - comp_bbox_reock, 4
 - comp_bc, 4
 - comp_box_reock, 5
 - comp_ch, 6
 - comp_components, 7
 - comp_corners, 7
 - comp_edges_rem, 8
 - comp_fh, 9
 - comp_frac_kept, 10
 - comp_holes, 11
 - comp_jagged, 12
 - comp_kiwysi, 12
 - comp_log_st, 13
 - comp_lw, 14
 - comp_polsby, 15
 - comp_reock, 16
 - comp_schwartz, 17
 - comp_skew, 18
 - comp_x_sym, 19
 - comp_y_sym, 20
 - prep_perims, 45
- * **competitiveness**
 - compet_talisman, 21
- * **data**
 - nh, 26
 - nh_m, 28
 - nh_map, 29
 - nh_plans, 31
- * **distances**
 - dist_euc, 22
 - dist_ham, 23
 - dist_info, 23
 - dist_man, 24
- * **incumbent**
 - inc_pairs, 25
- * **partisan**
 - part_bias, 31
 - part_decl, 32
 - part_decl_simple, 33
 - part_dil_asym, 34
 - part_dislocation, 35
 - part_dseats, 36
 - part_dvs, 37
 - part_egap, 37
 - part_egap_ep, 38
 - part_lop_wins, 39
 - part_mean_median, 40
 - part_resp, 41
 - part_rmd, 42
 - part_sscd, 43
 - part_tau_gap, 44
- * **segregation**
 - seg_dissim, 45
- * **splits**
 - splits_admin, 46
 - splits_count, 47
 - splits_district_fuzzy, 48
 - splits_multi, 49
 - splits_sub_admin, 49
 - splits_sub_count, 50
 - splits_sub_total, 51
 - splits_total, 52
- by_plan, 3
- comp_bbox_reock, 4
- comp_bc, 4
- comp_box_reock, 5
- comp_ch, 6
- comp_components, 7
- comp_corners, 7
- comp_edges_rem, 8
- comp_fh, 9
- comp_frac_kept, 10
- comp_holes, 11
- comp_jagged, 12
- comp_kiwysi, 12
- comp_log_st, 13

comp_lw, [14](#)
comp_polsby, [15](#)
comp_reock, [16](#)
comp_schwartz, [17](#)
comp_skew, [18](#)
comp_x_sym, [19](#)
comp_y_sym, [20](#)
compet_talisman, [21](#)

dist_euc, [22](#)
dist_ham, [23](#)
dist_info, [23](#)
dist_man, [24](#)

inc_pairs, [25](#)

list_fn, [26](#)

nh, [26](#)
nh_m, [28](#)
nh_map, [29](#)
nh_plans, [31](#)

part_bias, [31](#)
part_decl, [32](#)
part_decl_simple, [33](#)
part_dil_asym, [34](#)
part_dislocation, [35](#)
part_dseats, [36](#)
part_dvs, [37](#)
part_egap, [37](#)
part_egap_ep, [38](#)
part_lop_wins, [39](#)
part_mean_median, [40](#)
part_resp, [41](#)
part_rmd, [42](#)
part_sscd, [43](#)
part_tau_gap, [44](#)
prep_perims, [45](#)

seg_dissim, [45](#)
splits_admin, [46](#)
splits_count, [47](#)
splits_district_fuzzy, [48](#)
splits_multi, [49](#)
splits_sub_admin, [49](#)
splits_sub_count, [50](#)
splits_sub_total, [51](#)
splits_total, [52](#)

tally, [52](#)