

Package: vf (via r-universe)

July 3, 2024

Title Read Voter Files

Version 0.0.0.9000

Description States in the United States make full voter registries available as public information. This enables researchers to use voter files with clean, consistent formats. This package is focused on official voter files, rather than commercially available alternatives. Not all states are supported. The states which have readily available and free voter files are supported.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Imports cli, dplyr, fs, lubridate, purrr, readr, stringr, tidyr

URL <https://github.com/christopherkenny/vf>,
<http://christophertkenny.com/vf/>

BugReports <https://github.com/christopherkenny/vf/issues>

Repository <https://christopherkenny.r-universe.dev>

RemoteUrl <https://github.com/christopherkenny/vf>

RemoteRef HEAD

RemoteSha 9d86b06439d50f5197ea39c2fb734187fdb2be77

Contents

| | |
|----------------------|---|
| vf_read_fl | 2 |
| vf_read_nc | 2 |
| vf_read_ny | 3 |
| vf_read_oh | 3 |
| vf_read_ok | 4 |

| | |
|--------------|----------|
| Index | 5 |
|--------------|----------|

| | |
|------------|---------------------------|
| vf_read_fl | <i>Read FL voter file</i> |
|------------|---------------------------|

Description

Read FL voter file

Usage

```
vf_read_fl(path_detail, path_history, widen_history = TRUE)
```

Arguments

| | |
|--------------|--------------------------------------|
| path_detail | path to FL detail file or directory |
| path_history | path to FL history file or directory |

Value

tibble

Examples

```
# TODO
```

| | |
|------------|---------------------------|
| vf_read_nc | <i>Read NC voter file</i> |
|------------|---------------------------|

Description

Read NC voter file

Usage

```
vf_read_nc(path_registration, path_history, ...)
```

Arguments

| | |
|-------------------|--|
| path_registration | path to NC registration file or directory |
| path_history | path to NC history file or directory |
| ... | additional arguments passed to readr::read_csv() |

Value

tibble

Examples

```
# TODO
```

| | |
|------------|---------------------------|
| vf_read_ny | <i>Read NY voter file</i> |
|------------|---------------------------|

Description

Read NY voter file

Usage

```
vf_read_ny(path, ...)
```

Arguments

| | |
|------|--|
| path | path to NY voter file |
| ... | additional arguments passed to readr::read_csv() |

Value

tibble

Examples

```
# TODO
```

| | |
|------------|---------------------------|
| vf_read_oh | <i>Read OH voter file</i> |
|------------|---------------------------|

Description

Read OH voter file

Usage

```
vf_read_oh(path_registration, ...)
```

Arguments

| | |
|-------------------|--|
| path_registration | path to OH registration file or directory |
| ... | additional arguments passed to readr::read_csv() |

Value

tibble

Examples

```
# TODO
```

| | |
|------------|---------------------------|
| vf_read_ok | <i>Read OK voter file</i> |
|------------|---------------------------|

Description

Read OK voter file

Usage

```
vf_read_ok(path_registration, ...)
```

Arguments

path_registration
path to OK registration file or directory

...
additional arguments passed to readr::read_csv()

Value

tibble

Examples

```
# TODO
```

Index

vf_read_f1, 2
vf_read_nc, 2
vf_read_ny, 3
vf_read_oh, 3
vf_read_ok, 4